

Zeta125 Series

Pipe Lasers





Maximum productivity

- Fast self-levelling
- Automatic target alignment
- Cross axis compensation



IP68

Maximum robustness

- IP68 protection Full metal housing Built to last



Maximum flexibility

- Wide range of accessories
- Long distance remote control
- Safe and versatile charging options

f in y 🗖



geomax-positioning.com ©2018 Hexagon AB and/or its subsidiaries and affiliates. All rights reserved.

Zeta125 Series

With functional and versatile configuration, a full range of features and a tough design, the Zeta series fit all your needs, getting an error-free job done – no matter what the situation or the environmental conditions might be.



	Zeta125	Zeta125 US	Zeta125S
Self-levelling range	+45% to -15%		
Grade range	+40% to -10%		
Accuracy	±5 mm at 100 m (± 1/16" at 100') ; ± 10 arc sec.; ± .005%		
Cross axis levelling	Manual		Automatic (6°)
Vertical level	X		\checkmark
Autotarget system	Х		\checkmark
Manual alignment	X		\checkmark
Laser class	2	3R	3R
Protection	IP68		
Power supply	Rechargeable lithium ion battery pack 110/230V AC converter (charge and run simultaneously); 12V power cord		
Battery life	40h Li-Ion battery		
Thread mounting	5/8″		
Operating temperature	+50°C to -20°C (122°F to -4°F)		
Size and weight	305 (12″) x 105 (4.1″) x 113 mm (4.4″); 2.07 kg		
Operating range	>300m (985′)		
Detection angle	20° (12m / 40′ @30m / 100′)		
Rotation speed	1250 rpm		
REMOTE CONTROL			
Operating range	190 m (600') front through the pipe; 7.6 m (25') from rear		
Batteries	3 AA alkaline		
Dimensions	119 x 60 x 30 mm (4.7" x 2.35" x 1.2")		



08/18 842538 en Copyright GeoMax AG. Illustrations, descriptions and technical specifcations are not binding and may change. All trademarks and trade names are those of their respective owners.



Learn more at: geomax-positioning.com



GEOMAX AUTHORISED DISTRIBUTION PARTNER